

## 50 μL, Model 1705 RN SYR, Small Removable NDL, 22s ga, 2 in, point style 3

Specification Sheet (Part/REF # 80965)



The 1700 series syringes are the gas tight version of the original 700 series syringes. This series of gas tight syringes is ideal for dispensing volumes from 1  $\mu$ L up to 500  $\mu$ L. A variety of different terminations and needle options are available in this series.

## **Product Specifications**

Volume	50 μL
Syringe Type	Gastight
Syringe Series	1700
Termination	Removable Needle (RN)
Needle	Small RN
Gauge	22s gauge
Point Style	3
Needle Length	2 inch (51 mm)
Fluid Path	SST, borosilicate glass, PTFE
Autoclavable	Yes
Gas Sterilizable	Yes
Pressure	1000 psig (68.9 bar)
Maximum Temperature	115°C / 239°F
Minimum Temperature	10°C / 50°F
Barrel Inner Diameter	0.041 inches (1.03 mm)



US: +1-800-648-5950 EU: +40-356-635-055



Barrel Outer Diameter	0.305 inches (7.75 mm)	
Needle Inner Diameter	0.0059 inches (0.15 mm)	
Needle Outer Diameter	0.0283 inches (0.72 mm)	
Std Needle Dead Volume	1.13 μL	
Sales Quantity	1 syringe per pack	
Specifications are subject to change without notice		Spec. Version B

https://www.hamiltoncompany.com/laboratory-products/syringes/80965



US: +1-800-648-5950 EU: +40-356-635-055