



MX17VB6G

Key Specifications

Description	Viscosity Bath, 17 L, 6 Round
Controller Type	MX
Display	3.25" LCD
Languages Supported	English
Working Temperature Range °C	Ambient +10° to 135°
Temperature Stability °C	±0.07°
Temperature Calibration Capability	1-point
Working Access (L x W x D) (cm)	(6) x 5.1 Ø x 27.9 cm
Pump Type	Pressure
Flammability Class (DIN 12876-1)	I (NFL)

Key Features


MX Controller

Key Features

- Large, universal icon and English display
- On-screen prompts
- Single-point calibration capability

Vertical Tabs

Dependable & Intuitive Operation



Dependable & Intuitive Operation

An economical choice for routine laboratory applications, the MX Temperature Controller delivers

powerful circulation along with $\pm 0.07^{\circ}\text{C}$ temperature stability.

Three control buttons and plain-text on-screen prompts make the setup and operation of the MX Temperature Controller easy and straightforward.

Safe



Safe

User-settable high-temperature safety provides over-temperature and low liquid level protection. Patented, integrated design protects pump and heater while simplifying cleaning and maintenance.

Common Specifications

Working Temperature Range °F	Ambient +20° to 275°
Working Temperature Range °C	Ambient +10° to 135°
Reservoir Capacity (gallons)	4.49
Reservoir Capacity (liters)	17
Reservoir/Tank Material	Glass
Reservoir Cover	Round, Included
DuraTop	Yes
Working Access (L x W x D) (inches)	(6) x 2 Ø x 11 in
Working Access (L x W x D) (cm)	(6) x 5.1 Ø x 27.9 cm
Temperature Stability °F	$\pm 0.13^{\circ}$
Temperature Stability °C	$\pm 0.07^{\circ}$
Display	3.25" LCD
Display Resolution (Set)	0.1
Display Resolution (Read)	0.1
Pump Type	Pressure
Pump Speed	One
Process Connections	1/2" O.D. Barbed Tubes
Flammability Class (DIN 12876-1)	I (NFL)
Over-Temperature Protection / Failsafe Heater Control	Yes
Low Liquid Level Protection	Yes

Cooling Coil Port	Yes
Maximum Ambient Temperature °F	95°
Maximum Ambient Temperature °C	35°
Overall Dimensions (L x W x H) (inches)	12.5 Ø x 20.5 in
Overall Dimensions (L x W x H) (cm)	31.8 Ø x 52.1 cm
Environmental Compliance	RoHS, WEEE
Shipping Weight (pounds)	35.0
Shipping Weight (kilograms)	15.9
Catalog Page Number	70-71

50 Hz Only

Part Number	MX17VB6G-A12E
Maximum Pressure (psi)	1.8
Maximum Pressure (bar)	0.12
Maximum Pressure Flow Rate (gpm)	3.10
Maximum Pressure Flow Rate (l/min)	11.9
Included Hardware	Fitting Kit for External Applications
Heater Wattage	1100
Electrical Requirements (VAC/Hz/Ph/A)	240/50/1/6
Regulatory Approvals	CE

60 Hz Only

Part Number	MX17VB6G-A11B
Maximum Pressure (psi)	2.3
Maximum Pressure (bar)	0.16
Maximum Pressure Flow Rate (gpm)	3.60
Maximum Pressure Flow Rate (l/min)	13.5
Included Hardware	Fitting Kit for External Applications
Heater Wattage	1100
Electrical Requirements (VAC/Hz/Ph/A)	120/60/1/10
Regulatory Approvals	ETL



© 2015-2020 **PolyScience** 6600 W. Touhy Avenue, Niles, Illinois 60714-4516 USA

Phone: +1(847) 647-0611 or +1(800) 229-7569 **Fax:** +1(847) 647-1155

*/

Source URL (modified on 08/13/2021 - 13:44): <https://www.polyscience.com/specialty-product/17-liter-viscosity-bath>